



JIANGXI HITO SILICONE MATERIALS CO.,LTD

No 6 Tianhong road,Xinghuo

industry zone,Yongxiu,

Jiujiang,Jiangxi province,China

(86)792-3170326(Tel) (86) 792-3170355 (Fax)

TECHNICAL DATA SHEET

H-270

Wetting agent

DESCRIPTION

H-270 is substrate wetting agent. It can be used for water-based formulations, with good recoatability, can significantly improve wettability timber wood hole (in the wood coatings and thin coating), it can promote the flow of additional action, with low foaming.

TYPICAL PROPERTIES

Appearance	Colorless to light amber liquid
active ingredients %	100
Viscosity (25°C) mm ² /s	30-45
Surface Tension (0.1%wt), mN/m	<20.5
Density (25°C), g/cm ³	1.02-1.04

USES AND APPLICATION

Application system: water-based, solvent-based and solvent-free systems

Dosage: recommended dosage of 0.2 to 1.5% of the total formulation

SAFETY

Before handling, read the Material Safety Data Sheet and container label for safe use, physical and health hazard information.

STORAGE AND SHELF LIFE

After sealing packaging products stored in a cool, dry place, H-270 (Unbroken package) has a shelf life of 12 months from date of manufacture. After the expiration date, we can retest it, and if it meets the requirement, we can still use it. H-270 is transported as non-hazardous chemicals.

PACKAGING

H-270 is available in 200 kg/1000 kg plastic drum.

LEGAL DISCLAIMER

Hito chemical believes that the information in this technical data sheet is an accurate description of the typical uses of the product. Hito Chemical , however, disclaims any liability for incidental or consequential damages, which may result from the use of the product that are beyond its control. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual property right.



is a registered trademark of Hito Silicone Materials , China.